

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A multiparameter high precision concurrent estimation method in image subpixel matching in which in an N-dimensional similarity space where N (N is an integer of four or greater) correspondence parameters between images are axes, said N correspondence parameters between images are estimated ~~precisely and~~ concurrently by using an N-dimensional similarity value between images obtained at discrete positions, comprising the steps of:

determining a sub-sampling position where said N-dimensional similarity value between images is maximum or minimum on a line in parallel with a certain parameter axis, and determining an N-dimensional hyperplane that most approximates determined said sub-sampling position;

determining N of said N-dimensional hyperplanes with respect to each parameter axis;

determining an intersection point of N of said N-dimensional hyperplanes; ~~and~~ setting said intersection point as a sub-sampling grid estimation position for said correspondence parameter between images that gives a maximum value or a minimum value of N-dimensional similarity in said N-dimensional similarity space; and

displaying an image deformed by said N correspondence parameters between images that were estimated.

2. (currently amended) A three-parameter high precision concurrent estimation method in image subpixel matching in which in a three-dimensional similarity space where three correspondence parameters between images are axes, said three correspondence parameters between images are estimated ~~precisely and concurrently~~

by using a three-dimensional similarity value between images obtained at discrete positions, comprising the steps of:

- determining a sub-sampling position where said three-dimensional similarity value between images is maximum or minimum on a line in parallel with a certain parameter axis, and determining a plane that most approximates determined said sub-sampling position;

- determining three of said planes with respect to each parameter axis;

- determining an intersection point of three of said planes; and

- setting said intersection point as a sub-sampling grid estimation position for said correspondence parameter between images that gives a maximum value or a minimum value of three-dimensional similarity in said three-dimensional similarity space; and displaying an image deformed by said three correspondence parameters between images that were estimated.

3. (currently amended) A two-parameter high precision concurrent estimation method in image subpixel matching in which a position of displacements between images in horizontal and vertical directions that give a maximum value or a minimum value of a two-dimensional similarity in a continuous area is are estimated ~~precisely~~-by using a two-dimensional similarity value between images obtained discretely, comprising the steps of:

- determining a sub-sampling position where said two-dimensional similarity value between images is maximum or minimum on a line in parallel with a horizontal axis, and determining a line (horizontal extreme value line HEL) that most approximates determined said sub-sampling position;

- determining a sub-sampling position where said two-dimensional similarity value between images is maximum or minimum on a line in parallel with a vertical axis, and determining a line (vertical extreme value line VEL) that most approximates determined said sub-sampling position;

- determining an intersection point of said horizontal extreme value line HEL and said vertical extreme value line VEL; and

setting said intersection point as a subpixel estimation position for said displacements between images in horizontal and vertical directions that gives a maximum value or a minimum value of said two-dimensional similarity; and displaying an image deformed by said displacements between images in horizontal and vertical directions that were estimated.

4. (currently amended) A multiparameter high precision concurrent estimation computer program embodied in a computer-readable medium in image subpixel matching in which in an N-dimensional similarity space where N (N is an integer of four or greater) correspondence parameters between images are axes, said N correspondence parameters between images are estimated precisely-and-concurrently by using an N-dimensional similarity value between images obtained at discrete positions, said multiparameter high precision concurrent estimation computer program is executable with a computer, comprising the functions of:

determining a sub-sampling position where said N-dimensional similarity value between images is maximum or minimum on a line in parallel with a certain parameter axis, and determining an N-dimensional hyperplane that most approximates determined said sub-sampling position;

determining N of said N-dimensional hyperplanes with respect to each parameter axis;

determining an intersection point of N of said N-dimensional hyperplanes; and
setting said intersection point as a sub-sampling grid estimation position for said correspondence parameter between images that gives a maximum value or a minimum value of N-dimensional similarity in said N-dimensional similarity space; and displaying an image deformed by said N correspondence parameters between images that were estimated.

5. (currently amended) A three-parameter high precision concurrent estimation computer program embodied in a computer-readable medium in image subpixel matching in which in a three-dimensional similarity space where three

correspondence parameters between images are axes, said three correspondence parameters between images are estimated ~~precisely and~~ concurrently by using a three-dimensional similarity value between images obtained at discrete positions, said three-parameter high precision concurrent estimation computer program is executable with a computer, comprising the functions of:

- determining a sub-sampling position where said three-dimensional similarity value between images is maximum or minimum on a line in parallel with a certain parameter axis, and determining a plane that most approximates determined said sub-sampling position;

- determining three of said planes with respect to each parameter axis;

- determining an intersection point of three of said planes; and

- setting said intersection point as a sub-sampling grid estimation position for said correspondence parameter between images that gives a maximum value or a minimum value of three-dimensional similarity in said three-dimensional similarity space; and
displaying an image deformed by said three correspondence parameters between images that were estimated.

6. (currently amended) A two-parameter high precision concurrent estimation computer program embodied in a computer-readable medium in image subpixel matching in which a position of displacements between images in horizontal and vertical directions that give a maximum value or a minimum value of a two-dimensional similarity in a continuous area is are estimated ~~precisely~~ by using a two-dimensional similarity value between images obtained discretely, said two-parameter high precision concurrent estimation computer program is executable with a computer, comprising the functions of:

- determining a sub-sampling position where said two-dimensional similarity value between images is maximum or minimum on a line in parallel with a horizontal axis, and determining a line (horizontal extreme value line HEL) that most approximates determined said sub-sampling position;

determining a sub-sampling position where said two-dimensional similarity value between images is maximum or minimum on a line in parallel with a vertical axis, and determining a line (vertical extreme value line VEL) that most approximates determined said sub-sampling position;

determining an intersection point of said horizontal extreme value line HEL and said vertical extreme value line VEL; and

setting said intersection point as a subpixel estimation position for said displacements between images in horizontal and vertical directions that gives a maximum value or a minimum value of said two-dimensional similarity; and displaying an image deformed by said displacements between images in horizontal and vertical directions that were estimated.

7. (new) A multiparameter high precision concurrent estimation method in image subpixel matching in which in an N-dimensional similarity space where N (N is an integer of four or greater) correspondence parameters between images are axes, said N correspondence parameters between images are estimated concurrently by using an N-dimensional similarity value between images obtained at discrete positions, comprising the steps of:

determining a sub-sampling position where said N-dimensional similarity value between images is maximum or minimum on a line in parallel with a certain parameter axis, and determining an N-dimensional hyperplane that most approximates determined said sub-sampling position;

determining N of said N-dimensional hyperplanes with respect to each parameter axis;

determining an intersection point of N of said N-dimensional hyperplanes;

setting said intersection point as a sub-sampling grid estimation position for said correspondence parameter between images that gives a maximum value or a minimum value of N-dimensional similarity in said N-dimensional similarity space; and

displaying said N correspondence parameters between images that were estimated with numerical value.

8. (new) A three-parameter high precision concurrent estimation method in image subpixel matching in which in a three-dimensional similarity space where three correspondence parameters between images are axes, said three correspondence parameters between images are estimated concurrently by using a three-dimensional similarity value between images obtained at discrete positions, comprising the steps of:

- determining a sub-sampling position where said three-dimensional similarity value between images is maximum or minimum on a line in parallel with a certain parameter axis, and determining a plane that most approximates determined said sub-sampling position;

- determining three of said planes with respect to each parameter axis;

- determining an intersection point of three of said planes;

- setting said intersection point as a sub-sampling grid estimation position for said correspondence parameter between images that gives a maximum value or a minimum value of three-dimensional similarity in said three-dimensional similarity space; and

- displaying said three correspondence parameters between images that were estimated with numerical value.

9. (new) A two-parameter high precision concurrent estimation method in image subpixel matching in which displacements between images in horizontal and vertical directions that give a maximum value or a minimum value of a two-dimensional similarity in a continuous area are estimated by using a two-dimensional similarity value between images obtained discretely, comprising the steps of:

- determining a sub-sampling position where said two-dimensional similarity value between images is maximum or minimum on a line in parallel with a horizontal axis, and determining a line (horizontal extreme value line HEL) that most approximates determined said sub-sampling position;

determining a sub-sampling position where said two-dimensional similarity value between images is maximum or minimum on a line in parallel with a vertical axis, and determining a line (vertical extreme value line VEL) that most approximates determined said sub-sampling position;

determining an intersection point of said horizontal extreme value line HEL and said vertical extreme value line VEL; and

setting said intersection point as a subpixel estimation position for said displacements between images in horizontal and vertical directions that give a maximum value or a minimum value of said two-dimensional similarity; and

displaying said displacements between images in horizontal and vertical directions that were estimated with numerical value.

10. (new) A multiparameter high precision concurrent estimation computer program embodied in a computer-readable medium in image subpixel matching in which in an N-dimensional similarity space where N (N is an integer of four or greater) correspondence parameters between images are axes, said N correspondence parameters between images are estimated concurrently by using an N-dimensional similarity value between images obtained at discrete positions,

said multiparameter high precision concurrent estimation computer program is executable with a computer, comprising the functions of:

determining a sub-sampling position where said N-dimensional similarity value between images is maximum or minimum on a line in parallel with a certain parameter axis, and determining an N-dimensional hyperplane that most approximates determined said sub-sampling position;

determining N of said N-dimensional hyperplanes with respect to each parameter axis;

determining an intersection point of N of said N-dimensional hyperplanes;

setting said intersection point as a sub-sampling grid estimation position for said correspondence parameter between images that gives a maximum value or a minimum value of N-dimensional similarity in said N-dimensional similarity space; and

displaying said N correspondence parameters between images that were estimated with numerical value.

11. (new) A three-parameter high precision concurrent estimation computer program embodied in a computer-readable medium in image subpixel matching in which in a three-dimensional similarity space where three correspondence parameters between images are axes, said three correspondence parameters between images are estimated concurrently by using a three-dimensional similarity value between images obtained at discrete positions,

said three-parameter high precision concurrent estimation computer program is executable with a computer, comprising the functions of:

determining a sub-sampling position where said three-dimensional similarity value between images is maximum or minimum on a line in parallel with a certain parameter axis, and determining a plane that most approximates determined said sub-sampling position;

determining three of said planes with respect to each parameter axis;

determining an intersection point of three of said planes;

setting said intersection point as a sub-sampling grid estimation position for said correspondence parameter between images that gives a maximum value or a minimum value of three-dimensional similarity in said three-dimensional similarity space; and

displaying said N correspondence parameters between images that were estimated with numerical value.

12. (new) A two-parameter high precision concurrent estimation computer program embodied in a computer-readable medium in image subpixel matching in which displacements between images in horizontal and vertical directions that give a maximum value or a minimum value of a two-dimensional similarity in a continuous area are estimated by using a two-dimensional similarity value between images obtained discretely,

said two-parameter high precision concurrent estimation computer program is executable with a computer, comprising the functions of:

- determining a sub-sampling position where said two-dimensional similarity value between images is maximum or minimum on a line in parallel with a horizontal axis, and determining a line (horizontal extreme value line HEL) that most approximates determined said sub-sampling position;

- determining a sub-sampling position where said two-dimensional similarity value between images is maximum or minimum on a line in parallel with a vertical axis, and determining a line (vertical extreme value line VEL) that most approximates determined said sub-sampling position;

- determining an intersection point of said horizontal extreme value line HEL and said vertical extreme value line VEL; and

- setting said intersection point as a subpixel estimation position for said displacements between images in horizontal and vertical directions that give a maximum value or a minimum value of said two-dimensional similarity; and

- displaying said displacements between images in horizontal and vertical directions that were estimated with numerical value.